

NOTES

- 1. APPROACH END: FIRST 25'-O" OF TRAFFIC BARRIER AFFIXED TO BRIDGE STRUCTURE SHALL HAVE THE FIRST POST PLACED AT A MAXIMUM OF 1'-9" FROM THE BRIDGE AND THE NEXT SEVEN POSTS SPACED AT 3'-1'2" C/C. WHERE NECESSARY, AN ADDITIONAL OFFSET BRACKET MAY BE INSTALLED AT THE FOURTH AND FIFTH POSTS FROM THE BRIDGE TO AVOID CONFLICT WITH THE DRAINAGE INLETS. THIS TYPE OF "ANCHORAGE AT STRUCTURES" SHALL BE APPLIED TO ALL FOUR CORNERS OF THE BRIDGE STRUCTURE WHEREVER THERE IS TWO-WAY TRAFFIC, UNDIVIDED SECTION, OR NARROW DIVIDED SECTION WHEREBY AN ERRANT VEHICLE MAY REACH THE OPPOSITE CORNER OF THE BRIDGE STRUCTURE. WHEREVER THERE IS A BARRIER-DIVIDED SECTION OR WIDE DIVIDED SECTION WHEREBY AN ERRANT VEHICLE COULD NOT REACH THE OPPOSITE CORNER OF THE BRIDGE STRUCTURE, THIS TYPE OF "ANCHORAGE AT STRUCTURES" SHALL BE APPLIED ONLY AT THE APPROACH END WITH THE TRAILING ENDS TO BE TREATED AS DESIGNATED IN THE FOLLOWING NOTE.
- 2. TRAILING END: USE NORMAL POST SPACING. WHERE NECESSARY AN ADDITIONAL OFFSET BRACKET MAY BE INSTALLED AT THE SECOND POST TO AVOID CONFLICT WITH DRAINAGE INLETS.
- 3. ADDITIONAL OFFSET BRACKETS SHALL NOT EXCEED A MAXIMUM OF TWO PER POST IN ALL CASES.
- 4. COST OF ADDITIONAL POSTS AND OFFSET BRACKETS TO BE INCLUDED IN BID PRICE PER LINEAR FOOT OF TRAFFIC BARRIER WITH BEAM.
- 5. THE CONTRACTOR SHALL FURNISH AND INSTALL FOUR (4)⁷8" © HEAVY HEX. HEAD GALV. BOLTS WITH GALV. HEX. HEAD NUT AND GALV. RECTANGULAR WASHER CAST IN BRIDGE END POST. ATTACH W BEAM WITH GALV. RECTANGULAR WASHER AND HEX. NUT OR AS ALTERNATE THE CONTRACTOR SHALL FURNISH AND INSTALL FOUR (4) GALV. THREADED STUDS WITH GALV. RECTANGULAR WASHER AND TWO (2) GALV. HEX. NUTS CAST IN BRIDGE END POST. ATTACH W BEAM WITH GALV. RECTANGULAR WASHER AND GALV. HEX. NUT AS SHOWN IN ALTERNATE ANCHORAGE STUD DETAIL. STEEL SHALL CONFIRM TO ASTM-4307 AND IS HOT DIPPED GALV. TO ASTM-4123 AFTER FABRICATION.

| SPECIFICATION | CATEGORY CODE ITEMS | | | |
|---------------|---|---------|----------|-----------------------|
| 605 | | | | |
| APPROVED | Kill G. MECALL DIRECTOR - OFFICE OF HIGHWAY DEVELOPMENT | | | |
| State Highway | APPROVAL • SHA REVISIONS | | | FEDERAL MINISTRATION |
| | APPROVAL | 2-10-04 | APPROVAL | 4-26-83 |
| | REVISED | 8-16-12 | REVISED | 8-13-12 |
| | REVISED | | REVISED | · |
| | REVISED | • | REVISED | · |

Maryland Department of Transportation STATE HIGHWAY ADMINISTRATION

STANDARDS FOR HIGHWAYS AND INCIDENTAL STRUCTURES

TRAFFIC BARRIER W BEAM ANCHORAGE AT STRUCTURES

STANDARD NO.

MD-605.47